

NFE 3BBL STILL SYSTEM EQUIPMENT LIST

LOT NUMBER 2

01. **Distiller 3bbl** 1. Material: Sanitary TP2 copper and SS 304; 2. Heating way: Electric heating; 3. Working volume:3bbl; 4. Copper top, SS304 boiler and 5 pcs of copper column; 5. with gin basket, and condenser; 6. with pumps, pipes, valves, and other necessary fittings; 7. UL listed electric parts for American standard
02. **Single wall store tank 3bbl** 1.Sanitary Stainless steel 304, 2.Working volume: 3bbl; total volume: 3.6bbl; 3.Dome top head, dome bottom; 4.TIG excellent welding with argon shield; 5.Weld joint 0.4um polished. Tank interior is treated with acid passivation for keeping the best sanitation; 6.Single wall, thickness: 3mm; 7.Top manhole; 8.With 360 degree rotary CIP spray balls and arm; 9.Sample valve in the body; 10.Pressure relief valve; 11.Pressure gauge; 12.Temperature gauge; 13. four ss legs with screw assembly to adjust leg height
03. **Horizontal bright tank 3bbl** 1.Sanitary Stainless steel 304, 2.Working volume: 3bbl; total volume: 3.6bbl; 3.Horizontal type. Dome top head, dome bottom; 4.TIG excellent welding with argon shield; 5.Weld joint 0.4um polished. Tank interior is treated with acid passivation for keeping the best sanitation; 6.Double wall, insulation thickness:60mm.Internal tank:3mm,clodding tank:2mm; 7.Side manhole; 8.With 360 degree rotary CIP spray balls and arm; 9.Sample valve in the body; 10.Pressure relief valve; 11.Pressure gauge; 12.Temperature gauge; 13. four ss legs with screw assembly to adjust leg height
04. **Beer Pump with UL certificate Flow Rate:** 5m³/h Pump Lift: 24m Sanitary stainless steel grade pump, power 0.75kw, variable frequency control, Flow Rate: 5m³/h; Pump Lift: 24m, UL motor. Transfer beer from bright tank to boiler of distiller
05. **Beer hoses** 2m/set Sanitary food hose, with hose connectors